



Potentiometric Electrodes

eDAQ's range of potentiometric electrodes can be used with the:

- EP353 pH & ISE isoPod with e-corder and Chart software
- EPU353 USB pH & ISE isoPod and Pod-Vu software

to continuously record and display the sensor signals.

ET042 pH Electrode

A combination pH electrode, featuring an easy to clean double junction reference. This feature enables the electrode to be used to measure the pH in a wide variety of solutions, including low ionic strength, messy and biological samples.

pH Range:	0 to 14
Operating temperature:	0 to 60 °C
Cable length:	0.8 m (2.6')
Connector:	BNC



ET042 pH Electrode

ET5733 pH Electrode – Tuff-Tip®

A combination electrode featuring a novel Magna-Flow® reference junction and a rugged Tuff Tip® pH bulb. The large annular ceramic Magna-Flow® reference junction and cross linked polymer gel are resistant to fouling in harsh and dirty samples.

The Tuff Tip® pH bulb makes this electrode an excellent alternative to conventional pH electrodes in situations where there is a risk of bulb breakage, such as during undergraduate laboratory classes.

pH Range:	0 to 13
Operating temperature:	-5 to 100 °C
Cable length:	1.1 m (3.6')
Connector:	BNC



ET5733 pH Electrode – Tuff Tip

ET060 Redox Electrode

A combination redox (oxidation/reduction potential, ORP) electrode, with an easy to clean double junction reference and platinum wire sensor.

Operating temperature:	0 to 60 °C
Cable length:	1.1 m (2.6')
Connector:	BNC



ET060 Redox Electrode

www.eDAQ.com

E-mail: info@edaq.com

e-corder is a registered trademark of eDAQ Pty Ltd.
All other trademarks are the property of their respective owners. PT7/03

Document Number: M-ET/042/1115/060-0712
Copyright © eDAQ 2012